


NYLON SLINGS



HEAVY DUTY NYLON & POLYESTER SLINGS*
 1) Heavy Duty Web thickness is approximately 3/16".
 2) Eye length of Types 3 and 4 varies with sling width and number of webbing plies.

EYE LENGTH CHART



SLING WIDTH (IN)	PLIES OF WEBBING (IN)			
	1	2	3	4
1	8-1/2	8-1/2	10	10
2	10	10	12	12
3	11	11	14	14
4	12	12	16	16
5	14	14	18	18
6	16	16	18	18
8	20	20	24	24
10	24	24	24	24
12	24	24	24	24

TYPES 1 & 2

	WEB WIDTH (IN)	TYPE 1 (TC)	TYPE 2 (TT)	RATED CAPACITIES (LBS)		
				VERTICAL	CHOKER*	BASKET
1 PLY	2	TC1-802	TT1-802	3,200	2,400	6,400
	3	TC1-803	TT1-803	4,800	3,600	9,600
	4	TC1-804	TT1-804	6,400	4,800	12,800
	5	TC1-805	TT1-805	8,000	6,000	16,000
	6	TC1-806	TT1-806	9,600	7,200	19,200
	8	TC1-808	TT1-808	12,800	9,600	25,600
	10	TC1-810	TT1-810	16,000	12,000	32,000
	12	TC1-812	TT1-812	19,200	14,400	38,400
	16	TC1-816	TT1-816	25,500	19,200	51,000
2 PLY	2	TC2-802	TT2-802	6,400	4,800	12,800
	3	TC2-803	TT2-803	9,600	6,500	17,200
	4	TC2-804	TT2-804	11,500	8,600	23,000
	5	TC2-805	TT2-805	14,000	10,500	28,000
	6	TC2-806	TT2-806	16,800	12,600	33,600
	8	TC2-808	TT2-808	22,400	16,800	44,800
	10	TC2-810	TT2-810	28,000	21,000	56,000
	12	TC2-812	TT2-812	33,600	25,200	67,200
	16	TC2-816	TT2-816	44,800	33,600	89,600
3 PLY	18	TC3-818	TT3-818	50,400	37,800	100,800
	20	TC3-820	TT3-820	56,000	42,000	112,000
	24	TC3-824	TT3-824	67,200	50,400	134,400

Three & Four Ply Hardware Slings are Available upon Request.
 * Type Two cannot be used with a choker hitch.

WIDE LIFT (WL) SLINGS

	BODY WIDTH (IN)	STOCK NUMBER	VERTICAL BASKET CAPACITY (LBS)	EYE LENGTH (IN)	EYE MAT'L. WIDTH (IN)	
TYPE 8 CONTINUOUS EYE WIDE LIFT						
1 PLY	6	WL1-806	15,400	9	1-1/2	Continuous Eye Wide Lift For Heavy Loads Constructed from one endless sling with the two body lengths butted and joined side by side. Stiffener webbing is used at the base of the eyes to deter the body webbing from folding down the middle.
	8	WL1-808	20,400	12	2	
	10	WL1-810	25,600	15	2-1/2	
	12	WL1-812	30,800	18	2	
	16	WL1-816	38,000	24	2-3/4	
	20	WL1-820	45,000	30	3-1/2	
2 PLY	6	WL2-806	28,600	9	1-1/2	
	8	WL2-808	38,000	12	2	
	10	WL2-810	47,400	15	2-1/2	
	12	WL2-812	57,200	18	3	
	16	WL2-816	75,000	24	4	
	20	WL2-820	90,000	30	5	
1 PLY EYE	6	WLA1-806	5,000	6	1	Attached Eye Wide Lift For Light, Bulky Loads that require wider bearing areas and some balance attributes. Eyes are made from separate material - WLA1 is 1 ply - WLA2 is 2 ply - both sewn to sling body. Body is single ply for both 1 and 2 ply eyes.
	8	WLA1-808	5,000	8	1	
	10	WLA1-810	5,000	10	1	
	12	WLA1-812	5,000	12	1	
	16	WLA1-816	10,000	14	2	
	20	WLA1-820	10,000	16	2	
2 PLY EYE	6	WLA2-806	10,000	10	1	
	8	WLA2-808	10,000	10	1	
	10	WLA2-810	10,000	12	1	
	12	WLA2-812	10,000	12	1	
	16	WLA2-816	18,000	12	2	
	20	WLA2-820	18,000	18	2	

TYPES 3-FLAT EYE & 4-TWISTED EYE TYPE 5 ENDLESS

	WEB WIDTH (IN)	FLAT EYE TYPE 3 (EE)	TWISTED EYE TYPE 4 (TE)	RATED CAPACITIES (LBS)		
				VERTICAL	CHOKER	BASKET
1 PLY	1	EE1-801	TE1-801	1,600	1,200	3,200
	2	EE1-802	TE1-802	3,200	2,400	6,400
	3	EE1-803	TE1-803	4,800	3,600	9,600
	4	EE1-804	TE1-804	6,400	4,800	12,800
	5	EE1-805	TE1-805	8,000	6,000	16,000
	6	EE1-806	TE1-806	9,600	7,200	19,200
2 PLY	8	EE1-808	TE1-808	12,800	9,600	25,600
	10	EE1-810	TE1-810	16,000	12,000	32,000
	12	EE1-812	TE1-812	19,200	14,400	38,400
	1	EE2-801	TE2-801	3,200	2,400	6,400
	2	EE2-802	TE2-802	6,400	4,800	12,800
	3	EE2-803	TE2-803	8,600	6,500	17,200
3 PLY	4	EE2-804	TE2-804	11,500	8,600	23,000
	5	EE2-805	TE2-805	13,600	10,200	27,200
	6	EE2-806	TE2-806	16,300	12,200	32,600
	8	EE2-808	TE2-808	19,200	18,160	45,400
	10	EE2-810	TE2-810	28,400	22,700	68,200
	12	EE2-812	TE2-812	34,100	27,250	88,200
4 PLY	1	EE3-801	TE3-801	4,100	3,100	8,200
	2	EE3-802	TE3-802	8,300	6,200	16,600
	3	EE3-803	TE3-803	12,500	9,300	25,000
	4	EE3-804	TE3-804	16,000	12,000	32,000
	5	EE3-805	TE3-805	19,200	14,400	38,400
	6	EE3-806	TE3-806	23,000	17,200	46,000
5 PLY	8	EE3-808	TE3-808	30,700	23,000	61,400
	10	EE3-810	TE3-810	36,800	27,600	73,600
	12	EE3-812	TE3-812	44,000	33,000	88,000
	1	EE4-801	TE4-801	5,000	3,800	10,000
	2	EE4-802	TE4-802	10,000	7,500	20,000
	3	EE4-803	TE4-803	14,900	11,100	29,800
6 PLY	4	EE4-804	TE4-804	19,800	14,800	39,600
	5	EE4-805	TE4-805	24,800	18,600	49,600
	6	EE4-806	TE4-806	29,800	22,300	59,600
	8	EE4-808	TE4-808	39,700	29,700	79,400
	10	EE4-810	TE4-810	49,600	37,200	99,200
	12	EE4-812	TE4-812	59,500	44,600	119,000

REVERSED EYE (RE) SLINGS TYPE 6

Reversed Eye Sling is a modified endless sling. Cordura wear pads offer added protection on the body and eyes of the sling. This extra webbing offers superior abrasion resistance and sling life.

	SLING WIDTH (IN)	TYPE 6 (RE)	VERTICAL (LBS)	CHOKER (LBS)	BASKET (LBS)	SLING THKNS. (IN)	EYE LENGTH (IN)
HEAVY DUTY WEB							
1 PLY	2	RE1-802	4,500	3,600	9,000	5/16	9
	4	RE1-804	7,700	6,200	15,400	5/16	15
	6	RE1-806	11,000	8,800	22,000	5/16	15
2 PLY	2	RE2-802	6,500	5,200	13,000	1/2	9
	4	RE2-804	13,000	10,400	26,000	1/2	15
	6	RE2-806	20,000	16,000	40,000	1/2	15
3 PLY	4	RE3-804	16,400	13,100	32,800	11/16	15
	6	RE3-806	25,500	20,400	51,000	11/16	15
4 PLY	6	RE4-806	34,000	27,200	68,000	7/8	15
LIGHT DUTY WEB							
1 PLY	2	RE1-602	3,600	2,900	7,200	1/4	9
	3-1/2	RE1-603-1/2	5,000	4,000	10,000	1/4	12
	4	RE1-604	6,800	5,400	13,600	1/4	15
	6	RE1-606	8,000	6,400	16,000	1/4	15
2 PLY	2	RE2-602	5,200	4,200	10,400	3/8	9
	3-1/2	RE2-603-1/2	9,000	7,200	18,000	3/8	12
	4	RE2-604	10,500	8,400	21,000	3/8	15
	6	RE2-606	14,400	11,500	28,800	3/8	15
3 PLY	3-1/2	RE3-603-1/2	12,000	9,600	24,000	1/2	12
	4	RE3-604	14,000	11,200	28,000	1/2	15
	6	RE3-606	20,000	16,000	40,000	1/2	15



ORDERING NYLON SLINGS

HOW TO ORDER: Sling Part No _____ Length _____ Type _____

EXAMPLE: Sling Part No **EE2-802** Length **10'** Type **3**

Eye-Eye 2 Ply Heavy Duty Nylon 2" Wide - 10' Length - Flat Eye

NOTE: Measurement of Length does not include the ring

